

# ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779 + (631) 580-3191

344 MAIN ST., SUITE 101 + MT. KISCO, NY 10549 + (914) 666-8933

ELAP # 11681; NVLAP Lab Code 200531-0

## TEM AIR SAMPLE RESULTS

|               |                       |                |            |
|---------------|-----------------------|----------------|------------|
| CLIENT:       | Town of Islip         | SAMPLE DATE:   | 6/4/2014   |
| PROJECT NAME: | Roberto Clemente Park | DATE RECEIVED: | 6/4/2014   |
| AREA:         | Perimeter Monitoring  | SAMPLE TYPE:   | Ambient    |
| JOB #:        | 11114                 | SAMPLER:       | Edik Ivans |
| PAGE #:       | 1 of 3                | CUSTODY #:     | 10694      |

| Sample # | Sample Location | Start | End   | Run Time Minutes | Flow Rate Average | Volume Liters | Total Asbestos Structures | Type | # of structures > 5μ | # of structures >0.5μ <5μ | Filter Conc. S/mm <sup>2</sup> | Sensitivity S/cc | Air Conc. S/cc |
|----------|-----------------|-------|-------|------------------|-------------------|---------------|---------------------------|------|----------------------|---------------------------|--------------------------------|------------------|----------------|
| T1 IWA   | N perimeter     | 9:08  | 11:08 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T2 IWA   | N perimeter     | 9:08  | 11:08 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T3 IWA   | NW perimeter    | 9:13  | 11:13 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T4 IWA   | NW perimeter    | 9:13  | 11:13 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T5 IWA   | W perimeter     | 9:18  | 11:18 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T6 IWA   | W perimeter     | 9:18  | 11:18 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T7 IWA   | SW perimeter    | 9:24  | 11:24 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T8 IWA   | SW perimeter    | 9:24  | 11:24 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T9 IWA   | S perimeter     | 11:34 | 13:34 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, μ=micrometer  
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by:



Date Analyzed: 6/5/2014

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).

Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).

The data pertaining to these calculations can be found on the Asbestos Count Sheet.

The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.

The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.

A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

# ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779 + (631) 580-3191

344 MAIN ST., SUITE 101 + MT. KISCO, NY 10549 + (914) 666-8933

ELAP # 11681; NVLAP Lab Code 200531-0

## TEM AIR SAMPLE RESULTS

|               |                       |                |            |
|---------------|-----------------------|----------------|------------|
| CLIENT:       | Town of Islip         | SAMPLE DATE:   | 6/4/2014   |
| PROJECT NAME: | Roberto Clemente Park | DATE RECEIVED: | 6/4/2014   |
| AREA:         | Perimeter Monitoring  | SAMPLE TYPE:   | Ambient    |
| JOB #:        | 11114                 | SAMPLER:       | Edik Ivans |
| PAGE #:       | 2 of 3                | CUSTODY #:     | 10694      |

| Sample # | Sample Location | Start | End   | Run Time Minutes | Flow Rate Average | Volume Liters | Total Asbestos Structures | Type | # of structures > 5μ | # of structures >0.5μ <5μ | Filter Conc. S/mm <sup>2</sup> | Sensitivity S/cc | Air Conc. S/cc |
|----------|-----------------|-------|-------|------------------|-------------------|---------------|---------------------------|------|----------------------|---------------------------|--------------------------------|------------------|----------------|
| T10 IWA  | S perimeter     | 11:34 | 13:34 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T11 IWA  | SE perimeter    | 11:39 | 13:39 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T12 IWA  | SE perimeter    | 11:39 | 13:39 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T13 IWA  | E perimeter     | 11:43 | 13:43 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T14 IWA  | E perimeter     | 11:43 | 13:43 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T15 IWA  | NE perimeter    | 11:47 | 13:47 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T16 IWA  | NE perimeter    | 11:47 | 13:47 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T17      | Blank           |       |       |                  |                   |               |                           |      |                      |                           |                                |                  |                |
| T18      | Blank           |       |       |                  |                   |               |                           |      |                      |                           |                                |                  |                |

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, μ=micrometer  
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by:



Date Analyzed: 6/5/2014

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).

Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).

The data pertaining to these calculations can be found on the Asbestos Count Sheet.

The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.

The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.

A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

# ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779 + (631) 580-3191

344 MAIN ST., SUITE 101 + MT. KISCO, NY 10549 + (914) 666-8933

ELAP # 11681; NVLAP Lab Code 200531-0

## TEM AIR SAMPLE RESULTS

|               |                       |                |            |
|---------------|-----------------------|----------------|------------|
| CLIENT:       | Town of Islip         | SAMPLE DATE:   | 6/4/2014   |
| PROJECT NAME: | Roberto Clemente Park | DATE RECEIVED: | 6/4/2014   |
| AREA:         | Perimeter Monitoring  | SAMPLE TYPE:   | Ambient    |
| JOB #:        | 11114                 | SAMPLER:       | Edik Ivans |
| PAGE #:       | 3 of 3                | CUSTODY #:     | 10694      |

| Sample # | Sample Location | Start | End | Run Time Minutes | Flow Rate Average | Volume Liters | Total Asbestos Structures | Type | # of structures > 5 $\mu$ | # of structures >0.5 $\mu$ <5 $\mu$ | Filter Conc. S/mm <sup>2</sup> | Sensitivity S/cc | Air Conc. S/cc |
|----------|-----------------|-------|-----|------------------|-------------------|---------------|---------------------------|------|---------------------------|-------------------------------------|--------------------------------|------------------|----------------|
| T19      | Blank           |       |     |                  |                   |               |                           |      |                           |                                     |                                |                  |                |

S=Asbestos structures, cc=cubic centimeters, mm=millimeters,  $\mu$ =micrometer  
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by: Edward M. Schuster Date Analyzed: 6/5/2014

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).

Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).

The data pertaining to these calculations can be found on the Asbestos Count Sheet.

The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.

The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.

A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

# ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779 + (631) 580-3191

344 MAIN ST., SUITE 101 + MT. KISCO, NY 10549 + (914) 666-8933

ELAP # 11681; NVLAP Lab Code 200531-0

## TEM AIR SAMPLE RESULTS

|               |                       |                |                    |
|---------------|-----------------------|----------------|--------------------|
| CLIENT:       | Town of Islip         | SAMPLE DATE:   | 6/11/2014          |
| PROJECT NAME: | Roberto Clemente Park | DATE RECEIVED: | 6/11/2014          |
| AREA:         | Perimeter Monitoring  | SAMPLE TYPE:   | Ambient            |
| JOB #:        | 11114                 | SAMPLER:       | Driscoll / Johnson |
| PAGE #:       | 1 of 2                | CUSTODY #:     | 10765              |

| Sample # | Sample Location                 | Start | End   | Run Time Minutes | Flow Rate Average | Volume Liters | Total Asbestos Structures | Type | # of structures > 5μ | # of structures >0.5μ <5μ | Filter Conc. S/mm <sup>2</sup> | Sensitivity S/cc | Air Conc. S/cc |
|----------|---------------------------------|-------|-------|------------------|-------------------|---------------|---------------------------|------|----------------------|---------------------------|--------------------------------|------------------|----------------|
| 1A IWA   | North perimeter west of pool    | 9:38  | 11:40 | 122              | 10                | 1220          | 0                         |      | 0                    | 0                         | 0                              | .0042            | <.0042         |
| 2A IWA   | North perimeter west of pool    | 9:42  | 11:42 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| 3A IWA   | North perimeter pool area       | 9:50  | 11:58 | 128              | 10                | 1280          | 0                         |      | 0                    | 0                         | 0                              | .004             | <.004          |
| 4A IWA   | East perimeter pool area        | 9:51  | 11:58 | 127              | 10                | 1270          | 0                         |      | 0                    | 0                         | 0                              | .0041            | <.0041         |
| 5A IWA   | East perimeter pool area        | 10:00 | 12:04 | 124              | 10                | 1240          | 0                         |      | 0                    | 0                         | 0                              | .0042            | <.0042         |
| 6A IWA   | East perimeter pool area        | 10:01 | 12:04 | 123              | 10                | 1230          | 0                         |      | 0                    | 0                         | 0                              | .0042            | <.0042         |
| 7A IWA   | East perimeter parking lot      | 10:12 | 12:27 | 135              | 10                | 1350          | 0                         |      | 0                    | 0                         | 0                              | .0038            | <.0038         |
| 8A IWA   | East perimeter pool house       | 10:13 | 12:31 | 138              | 10                | 1380          | 0                         |      | 0                    | 0                         | 0                              | .0037            | <.0037         |
| 9A IWA   | West perimeter basketball court | 11:54 | 13:56 | 122              | 10                | 1220          | 0                         |      | 0                    | 0                         | 0                              | .0042            | <.0042         |

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, μ=micrometer  
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by:



Date Analyzed: 6/12/2014

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).

Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).

The data pertaining to these calculations can be found on the Asbestos Count Sheet.

The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.

The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.

A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

# ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779 + (631) 580-3191

344 MAIN ST., SUITE 101 + MT. KISCO, NY 10549 + (914) 666-8933

ELAP # 11681; NVLAP Lab Code 200531-0

## TEM AIR SAMPLE RESULTS

|               |                       |                |                    |
|---------------|-----------------------|----------------|--------------------|
| CLIENT:       | Town of Islip         | SAMPLE DATE:   | 6/11/2014          |
| PROJECT NAME: | Roberto Clemente Park | DATE RECEIVED: | 6/11/2014          |
| AREA:         | Perimeter Monitoring  | SAMPLE TYPE:   | Ambient            |
| JOB #:        | 11114                 | SAMPLER:       | Driscoll / Johnson |
| PAGE #:       | 2 of 2                | CUSTODY #:     | 10765              |

| Sample # | Sample Location                 | Start | End   | Run Time Minutes | Flow Rate Average | Volume Liters | Total Asbestos Structures | Type | # of structures > 5μ | # of structures >0.5μ <5μ | Filter Conc. S/mm <sup>2</sup> | Sensitivity S/cc | Air Conc. S/cc |
|----------|---------------------------------|-------|-------|------------------|-------------------|---------------|---------------------------|------|----------------------|---------------------------|--------------------------------|------------------|----------------|
| 10A IWA  | West perimeter basketball court | 11:54 | 13:56 | 122              | 10                | 1220          | 0                         |      | 0                    | 0                         | 0                              | .0042            | <.0042         |
| 11A IWA  | West grass area by fence        | 12:16 | 14:16 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| 12A IWA  | West grass area by fence        | 12:16 | 14:16 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| 13A IWA  | South recharge basin path       | 12:23 | 14:23 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| 14A IWA  | South recharge basin path       | 12:23 | 14:23 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| 15A IWA  | South baseball field perimeter  | 12:37 | 14:37 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| 16A IWA  | South baseball field perimeter  | 12:37 | 14:37 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| 17A      | Blank inside                    |       |       |                  |                   |               |                           |      |                      |                           |                                |                  |                |
| 18A      | Blank sealed                    |       |       |                  |                   |               |                           |      |                      |                           |                                |                  |                |

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, μ=micrometer  
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by: Edward M. Schuster Date Analyzed: 6/12/2014

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).

Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).

The data pertaining to these calculations can be found on the Asbestos Count Sheet.

The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.

The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.

A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

# ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779 + (631) 580-3191

344 MAIN ST., SUITE 101 + MT. KISCO, NY 10549 + (914) 666-8933

ELAP # 11681; NVLAP Lab Code 200531-0

## TEM AIR SAMPLE RESULTS

|               |                       |                |            |
|---------------|-----------------------|----------------|------------|
| CLIENT:       | Town of Islip         | SAMPLE DATE:   | 6/18/2014  |
| PROJECT NAME: | Roberto Clemente Park | DATE RECEIVED: | 6/18/2014  |
| AREA:         | Perimeter Monitoring  | SAMPLE TYPE:   | Ambient    |
| JOB #:        | 11114                 | SAMPLER:       | Edik Ivans |
| PAGE #:       | 1 of 2                | CUSTODY #:     | 10851      |

| Sample # | Sample Location     | Start | End   | Run Time Minutes | Flow Rate Average | Volume Liters | Total Asbestos Structures | Type | # of structures > 5μ | # of structures >0.5μ <5μ | Filter Conc. S/mm <sup>2</sup> | Sensitivity S/cc | Air Conc. S/cc |
|----------|---------------------|-------|-------|------------------|-------------------|---------------|---------------------------|------|----------------------|---------------------------|--------------------------------|------------------|----------------|
| T1 IWA   | North Perimeter     | 9:30  | 11:30 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T2 IWA   | North Perimeter     | 9:30  | 11:30 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T3 IWA   | Northeast Perimeter | 9:33  | 11:33 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T4 IWA   | Northeast Perimeter | 9:33  | 11:33 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T5 IWA   | East Perimeter      | 9:36  | 11:36 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T6 IWA   | East Perimeter      | 9:36  | 11:36 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T7 IWA   | Southeast Perimeter | 9:40  | 11:40 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T8 IWA   | Southeast Perimeter | 9:40  | 11:40 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T9 IWA   | Northwest Perimeter | 11:50 | 13:50 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, μ=micrometer  
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by:



Date Analyzed: 6/19/2014

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).

Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).

The data pertaining to these calculations can be found on the Asbestos Count Sheet.

The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.

The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.

A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

# ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779 + (631) 580-3191

344 MAIN ST., SUITE 101 + MT. KISCO, NY 10549 + (914) 666-8933

ELAP # 11681; NVLAP Lab Code 200531-0

## TEM AIR SAMPLE RESULTS

|               |                       |                |            |
|---------------|-----------------------|----------------|------------|
| CLIENT:       | Town of Islip         | SAMPLE DATE:   | 6/18/2014  |
| PROJECT NAME: | Roberto Clemente Park | DATE RECEIVED: | 6/18/2014  |
| AREA:         | Perimeter Monitoring  | SAMPLE TYPE:   | Ambient    |
| JOB #:        | 11114                 | SAMPLER:       | Edik Ivans |
| PAGE #:       | 2 of 2                | CUSTODY #:     | 10851      |

| Sample # | Sample Location     | Start | End   | Run Time Minutes | Flow Rate Average | Volume Liters | Total Asbestos Structures | Type | # of structures > 5μ | # of structures >0.5μ <5μ | Filter Conc. S/mm <sup>2</sup> | Sensitivity S/cc | Air Conc. S/cc |
|----------|---------------------|-------|-------|------------------|-------------------|---------------|---------------------------|------|----------------------|---------------------------|--------------------------------|------------------|----------------|
| T10 IWA  | Northwest Perimeter | 11:50 | 13:50 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T11 IWA  | West Perimeter      | 11:53 | 13:53 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T12 IWA  | West Perimeter      | 11:53 | 13:53 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T13 IWA  | Southwest Perimeter | 11:57 | 13:57 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T14 IWA  | Southwest Perimeter | 11:57 | 13:57 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T15 IWA  | South Perimeter     | 12:02 | 14:02 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T16 IWA  | South Perimeter     | 12:02 | 14:02 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T17      | Blank               |       |       |                  |                   |               | 0                         |      | 0                    | 0                         | 0                              |                  |                |
| T18      | Opened Field Blank  |       |       |                  |                   |               | 0                         |      | 0                    | 0                         | 0                              |                  |                |

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, μ=micrometer  
≤less than, >greater than, Flow Rate in liters per minute

Analyzed by:



Date Analyzed: 6/19/2014

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).

Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).

The data pertaining to these calculations can be found on the Asbestos Count Sheet.

The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.

The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.

A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

# ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779 + (631) 580-3191

344 MAIN ST., SUITE 101 + MT. KISCO, NY 10549 + (914) 666-8933

ELAP # 11681; NVLAP Lab Code 200531-0

## TEM AIR SAMPLE RESULTS

|               |                       |                |            |
|---------------|-----------------------|----------------|------------|
| CLIENT:       | Town of Islip         | SAMPLE DATE:   | 6/25/2014  |
| PROJECT NAME: | Roberto Clemente Park | DATE RECEIVED: | 6/25/2014  |
| AREA:         | Perimeter Monitoring  | SAMPLE TYPE:   | Ambient    |
| JOB #:        | 11114                 | SAMPLER:       | Edik Ivans |
| PAGE #:       | 1 of 2                | CUSTODY #:     | 10919      |

| Sample # | Sample Location     | Start | End   | Run Time Minutes | Flow Rate Average | Volume Liters | Total Asbestos Structures | Type | # of structures > 5μ | # of structures >0.5μ <5μ | Filter Conc. S/mm <sup>2</sup> | Sensitivity S/cc | Air Conc. S/cc |
|----------|---------------------|-------|-------|------------------|-------------------|---------------|---------------------------|------|----------------------|---------------------------|--------------------------------|------------------|----------------|
| T1 IWA   | North Perimeter     | 9:20  | 11:20 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T2 IWA   | North Perimeter     | 9:20  | 11:20 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T3 IWA   | Northeast Perimeter | 9:23  | 11:23 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T4 IWA   | Northeast Perimeter | 9:23  | 11:23 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T5 IWA   | East Perimeter      | 9:26  | 11:26 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T6 IWA   | East Perimeter      | 9:26  | 11:26 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T7 IWA   | Southeast Perimeter | 9:30  | 11:30 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T8 IWA   | Southeast Perimeter | 9:30  | 11:30 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T9 IWA   | West Perimeter      | 11:37 | 13:37 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, μ=micrometer  
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by:

Date Analyzed: 6/26/2014

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).

Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).

The data pertaining to these calculations can be found on the Asbestos Count Sheet.

The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.

The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.

A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

# ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779 + (631) 580-3191

344 MAIN ST., SUITE 101 + MT. KISCO, NY 10549 + (914) 666-8933

ELAP # 11681; NVLAP Lab Code 200531-0

## TEM AIR SAMPLE RESULTS

|               |                       |                |            |
|---------------|-----------------------|----------------|------------|
| CLIENT:       | Town of Islip         | SAMPLE DATE:   | 6/25/2014  |
| PROJECT NAME: | Roberto Clemente Park | DATE RECEIVED: | 6/25/2014  |
| AREA:         | Perimeter Monitoring  | SAMPLE TYPE:   | Ambient    |
| JOB #:        | 11114                 | SAMPLER:       | Edik Ivans |
| PAGE #:       | 2 of 2                | CUSTODY #:     | 10919      |

| Sample # | Sample Location     | Start | End   | Run Time Minutes | Flow Rate Average | Volume Liters | Total Asbestos Structures | Type | # of structures > 5μ | # of structures >0.5μ <5μ | Filter Conc. S/mm <sup>2</sup> | Sensitivity S/cc | Air Conc. S/cc |
|----------|---------------------|-------|-------|------------------|-------------------|---------------|---------------------------|------|----------------------|---------------------------|--------------------------------|------------------|----------------|
| T10 IWA  | West Perimeter      | 11:37 | 13:37 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T11 IWA  | Southwest Perimeter | 11:41 | 13:41 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T12 IWA  | Southwest Perimeter | 11:41 | 13:41 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T13 IWA  | South Perimeter     | 11:45 | 13:45 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T14 IWA  | South Perimeter     | 11:45 | 13:45 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T15 IWA  | South Perimeter     | 11:49 | 13:49 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T16 IWA  | South Perimeter     | 11:49 | 13:49 | 120              | 10                | 1200          | 0                         |      | 0                    | 0                         | 0                              | .0043            | <.0043         |
| T17      | Sealed Blank        |       |       |                  |                   |               |                           |      |                      |                           |                                |                  |                |
| T18      | Opened Field Blank  |       |       |                  |                   |               |                           |      |                      |                           |                                |                  |                |

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, μ=micrometer  
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by:

Date Analyzed: 6/26/2014

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).

Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).

The data pertaining to these calculations can be found on the Asbestos Count Sheet.

The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.

The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.

A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.